



SB シャックル

BB シャックル

呼び径 mm(T)	B	L	L1	d1	ネジ径	D	使用荷重		重量(kg)	
							tf	kN	SB	BB
10	17	40	54	12	M12	25	1.25	12.25	0.18	0.24
12	20	48	63	15	M14	32	2.5	24.5	0.32	0.39
14	24	56	72	17	M16	36	3.15	30.87	0.47	0.59
16	26	64	80	19	M18	40	4.0	39.2	0.67	0.82
18	29	72	95	21	M20	45	5.0	49.0	0.90	1.30
20	31	80	104	24	M24	50	6.3	61.74	1.30	1.80
22	34	88	117	26	M24	55	7	68.6	1.9	2.20
24	39	96	126	30	M30	62	8	78.4	2.6	3.0
26	41	104	135	32	M30	66	10.0	98	2.9	3.6
28	43	112	144	34	M33	70	12.5	122.5	3.6	4.4
30	45	120	153	36	M36	75	14	137.2	4.4	5.3
32	48	128	167	38	M36	80	16	156.8	5.1	6.8
34	50	136	176	40	M39	85	18	176.4	6.2	8.1
36	54	144	190	42	M42	90	20	196	7.5	9.8
38	57	152	198	46	M45	95	22	215.6	9.0	11.5
40	60	160	212	48	M48	100	25	245	10.6	14.2
42	63	168	220	51	M48	105	27	264.6	11.9	15.9
44	66	176	230	54	M48	110	31.5	308.7	13.4	18.8
46	68	184	240	56	M48	115	32	313.6	15.0	20.00
48	72	192	248	58	M56	120	34	333.2	17.9	22.90
50	75	200	257	60	M56	125	40	392	19.9	26.40
55	83	220	280	65	M64	138	45	441	26.5	34.80
60	90	240	310	70	M64	150	50	490	33.0	42.60
65	98	260	338	77	M72	164	63	617.4	42.9	55.60
70	105	280	360	83	M80	178	80	784	56.0	73.70
75	112	300	387	90	M80	192	90	882	65.6	87.00
80	120	320	414	96	M90	206	100	980	83.0	108.00
85	128	340	440	102	M90	220	110	1078	94.7	126.00
90	135	360	473	108	M100	232	125	1225	115.0	152.00